



▶ PATRIOT™ GELCOAT SYSTEM

The Patriot™ Gelcoat System delivers unprecedented precision, power, versatility and rugged construction for long-lasting use.

DESCRIPTION:

▶ SYSTEM FEATURES

The Patriot™ Gelcoat System features a deep induction heat hardened Fluid Section which is then coated with a thick hard chrome layer to increase the wear characteristics of the system, allowing it to run for longer periods.

Available in Internal & External Mix Configurations

- Unique Patriot™ pumping system
- Catalyst-to-resin variances less than 1%
- Lower production costs
- Versatile modular components

▶ SPECIFICATIONS

PATRIOT™ GELCOAT SYSTEM

Output Capabilities: 1.5 LBS/MIN - 7 LBS/MIN
(.68 KGS/MIN - 1.49 KGS/MIN)

Avg. Air Consumption: 8 CFM (0.23 m³/MIN)

Catalyst % Range: .75-2.5% by volume

Available Pump Ratios: 15:1 & 30:1

Maximum Air Input Pressure: 100 PSI (7BAR)

▶ OPTIONS

Heaters

- CFH Series

Monitors

- CB-8000
- Catalyst Alarms
- CTS-9000

Mixers

- M-AGD

Guns

- TLN Series
- PRO Series
- AT Series



Knoxville

Corporate Headquarters
2030 Falling Waters Rd., Suite 350
Knoxville, TN 37932
865-686-5670

Kent

Manufacturing Center
1862 Ives Ave.
Kent, WA 98032
253-854-2660

Knoxville

Service Center
642 Barbrow Lane
Knoxville, TN 37932
865-321-8809

Goshen

Service Center
320 North Main St.
Goshen, IN 46528
574-534-1434

Oldsmar

Service Center
146 Dunbar Avenue, Unit A
Oldsmar, FL 34677
727-573-2955

Canada

72 Beauvais
Delson, Qc J5B 1W8
888.538.4330

▶ For more information about adding the Patriot™ Gelcoat System to your operation, or any of your adhesive dispensing needs, visit Magnum Venus Products at www.mvpind.com.